

```
[oracle@ol6-agrac-rac1 ~]$ gedit ~/.bash_profile
[oracle@ol6-agrac-rac1 ~]$ cat ~/.bash_profile
# .bash_profile

# Get the aliases and functions
if [ -f ~/.bashrc ]; then
    . ~/.bashrc
fi

# User specific environment and startup programs

PATH=$PATH:$HOME/bin

export PATH

TMP=/tmp; export TMP
TMPDIR=$TMP; export TMPDIR

ORACLE_HOSTNAME=ol6-agrac-rac1.localdomain; export ORACLE_HOSTNAME
ORACLE_UNQNAME=RAC; export ORACLE_UNQNAME
ORACLE_BASE=/u01/app/oracle; export ORACLE_BASE
GRID_HOME=/u01/app/11.2.0.3/grid; export GRID_HOME
DB_HOME=$ORACLE_BASE/product/11.2.0.3/db_1; export DB_HOME
ORACLE_HOME=$DB_HOME; export ORACLE_HOME
ORACLE_SID=RAC1; export ORACLE_SID
ORACLE_TERM=xterm; export ORACLE_TERM

BASE_PATH=/usr/sbin:$PATH; export BASE_PATH
PATH=$ORACLE_HOME/bin:$BASE_PATH; export PATH

LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib; export LD_LIBRARY_PATH
CLASSPATH=$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib; export CLASSPATH

if [ $USER = "oracle" ]; then
    if [ $SHELL = "/bin/ksh" ]; then
        ulimit -p 16384
        ulimit -n 65536
    else
        ulimit -u 16384 -n 65536
    fi
fi
```

```
[oracle@ol6-agrac-rac1 ~]$ gedit ~/.bashrc
[oracle@ol6-agrac-rac1 ~]$ cat ~/.bashrc
# .bashrc

# Source global definitions
if [ -f /etc/bashrc ]; then
    . /etc/bashrc
fi

# User specific aliases and functions

alias grid_env='. /home/oracle/grid_env'
alias db_env='. /home/oracle/db_env'
[oracle@ol6-agrac-rac1 ~]$ █
```

File Edit View Search Terminal Help

```
[oracle@ol6-agrac-rac1 ~]$ gedit ~/grid_env
```

```
[oracle@ol6-agrac-rac1 ~]$ cat ~/grid_env
```

```
ORACLE_SID=+ASM1; export ORACLE_SID
ORACLE_HOME=$GRID_HOME; export ORACLE_HOME
PATH=$ORACLE_HOME/bin:$BASE_PATH; export PATH
```

```
LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib; export LD_LIBRARY_PATH
CLASSPATH=$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib; export CLASSPATH
```

```
[oracle@ol6-agrac-rac1 ~]$ gedit ~/db_env
```

```
[oracle@ol6-agrac-rac1 ~]$ cat ~/db_env
```

```
ORACLE_SID=RAC1; export ORACLE_SID
ORACLE_HOME=$DB_HOME; export ORACLE_HOME
PATH=$ORACLE_HOME/bin:$BASE_PATH; export PATH
```

```
LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib; export LD_LIBRARY_PATH
CLASSPATH=$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib; export CLASSPATH
```

```
[oracle@ol6-agrac-rac1 ~]$ █
```

```
[oracle@ool6-agrac-rac1 ~]$ reboot
```

File Edit View Search Terminal Help

```
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_HOSTNAME
ol6-agrac-rac1.localdomain
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_BASE
/u01/app/oracle
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_HOME
/u01/app/oracle/product/11.2.0.3/db_1
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_UNQNAME
RAC
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_SID
RAC1
[oracle@ol6-agrac-rac1 ~]$ echo $BASE_PATH
/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/sbin:/sbin:/home/oracle/bin
[oracle@ol6-agrac-rac1 ~]$ echo $PATH
/u01/app/oracle/product/11.2.0.3/db_1/bin:/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/s
bin:/sbin:/home/oracle/bin
[oracle@ol6-agrac-rac1 ~]$ echo $GRID_HOME
/u01/app/11.2.0.3/grid
[oracle@ol6-agrac-rac1 ~]$ grid_env
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_HOME
/u01/app/11.2.0.3/grid
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_SID
+ASM1
[oracle@ol6-agrac-rac1 ~]$ echo $PATH
/u01/app/11.2.0.3/grid/bin:/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/sbin:/sbin:/home
/oracle/bin
[oracle@ol6-agrac-rac1 ~]$ db_env
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_HOME
/u01/app/oracle/product/11.2.0.3/db_1
[oracle@ol6-agrac-rac1 ~]$ echo $ORACLE_SID
RAC1
[oracle@ol6-agrac-rac1 ~]$ echo $PATH
/u01/app/oracle/product/11.2.0.3/db_1/bin:/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/s
bin:/sbin:/home/oracle/bin
[oracle@ol6-agrac-rac1 ~]$
```

```
[oracle@ol6-agrac-rac1 ~]$ scp ./bash_profile oracle@ol6-agrac-rac2:/home/oracle
bash_profile 100% 993 1.0KB/s 00:00
[oracle@ol6-agrac-rac1 ~]$ scp ./bashrc oracle@ol6-agrac-rac2:/home/oracle
bashrc 100% 203 0.2KB/s 00:00
[oracle@ol6-agrac-rac1 ~]$ scp ./grid_env oracle@ol6-agrac-rac2:/home/oracle
grid_env 100% 267 0.3KB/s 00:00
[oracle@ol6-agrac-rac1 ~]$ scp ./db_env oracle@ol6-agrac-rac2:/home/oracle
db_env 100% 264 0.3KB/s 00:00
[oracle@ol6-agrac-rac1 ~]$ █
```

```
if [ -f ~/.bashrc ]; then
    . ~/.bashrc
fi

# User specific environment and startup programs

PATH=$PATH:$HOME/bin

export PATH

TMP=/tmp; export TMP
TMPDIR=$TMP; export TMPDIR

ORACLE_HOSTNAME=ol6-agrac-rac2.localdomain; export ORACLE_HOSTNAME
ORACLE_UNQNAME=RAC; export ORACLE_UNQNAME
ORACLE_BASE=/u01/app/oracle; export ORACLE_BASE
GRID_HOME=/u01/app/11.2.0.3/grid; export GRID_HOME
DB_HOME=$ORACLE_BASE/product/11.2.0.3/db_1; export DB_HOME
ORACLE_HOME=$DB_HOME; export ORACLE_HOME
ORACLE_SID=RAC2; export ORACLE_SID
ORACLE_TERM=xterm; export ORACLE_TERM

BASE_PATH=/usr/sbin:$PATH; export BASE_PATH
PATH=$ORACLE_HOME/bin:$BASE_PATH; export PATH

LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib; export LD_LIBRARY_PATH
CLASSPATH=$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib; export CLASSPATH

if [ $USER = "oracle" ]; then
    if [ $SHELL = "/bin/ksh" ]; then
        ulimit -p 16384
        ulimit -n 65536
    else
        ulimit -u 16384 -n 65536
    fi
fi
```

```
[oracle@ol6-agrac-rac2 ~]$ gedit ~/.bashrc
[oracle@ol6-agrac-rac2 ~]$ cat ~/.bashrc
# .bashrc

# Source global definitions
if [ -f /etc/bashrc ]; then
    . /etc/bashrc
fi

# User specific aliases and functions

alias grid_env='. /home/oracle/grid_env'
alias db_env='. /home/oracle/db_env'
[oracle@ol6-agrac-rac2 ~]$ █
```



```
[oracle@ol6-agrac-rac2 ~]$ gedit ~/grid_env
[oracle@ol6-agrac-rac2 ~]$ cat ~/grid_env
ORACLE_SID=+ASM2; export ORACLE_SID
ORACLE_HOME=$GRID_HOME; export ORACLE_HOME
PATH=$ORACLE_HOME/bin:$BASE_PATH; export PATH
```

```
LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib; export LD_LIBRARY_PATH
CLASSPATH=$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib; export CLASSPATH
```

```
[oracle@ol6-agrac-rac2 ~]$ gedit ~/db_env
[oracle@ol6-agrac-rac2 ~]$ cat ~/db_env
ORACLE_SID=RAC2; export ORACLE_SID
ORACLE_HOME=$DB_HOME; export ORACLE_HOME
PATH=$ORACLE_HOME/bin:$BASE_PATH; export PATH
```

```
LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib; export LD_LIBRARY_PATH
CLASSPATH=$ORACLE_HOME/jlib:$ORACLE_HOME/rdbms/jlib; export CLASSPATH
[oracle@ol6-agrac-rac2 ~]$ █
```

```
[oracle@016-agrac-rac2 ~]$ reboot
```

File Edit View Search Terminal Help

```
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_HOSTNAME
ol6-agrac-rac2.localdomain
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_BASE
/u01/app/oracle
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_HOME
/u01/app/oracle/product/11.2.0.3/db_1
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_UNQNAME
RAC
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_SID
RAC2
[oracle@ol6-agrac-rac2 ~]$ echo $BASE_PATH
/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/sbin:/sbin:/home/oracle/bin
[oracle@ol6-agrac-rac2 ~]$ echo $PATH
/u01/app/oracle/product/11.2.0.3/db_1/bin:/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/s
bin:/sbin:/home/oracle/bin
[oracle@ol6-agrac-rac2 ~]$ echo $GRID_HOME
/u01/app/11.2.0.3/grid
[oracle@ol6-agrac-rac2 ~]$ grid_env
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_HOME
/u01/app/11.2.0.3/grid
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_SID
+ASM2
[oracle@ol6-agrac-rac2 ~]$ echo $PATH
/u01/app/11.2.0.3/grid/bin:/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/sbin:/sbin:/home
/oracle/bin
[oracle@ol6-agrac-rac2 ~]$ db_env
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_HOME
/u01/app/oracle/product/11.2.0.3/db_1
[oracle@ol6-agrac-rac2 ~]$ echo $ORACLE_SID
RAC2
[oracle@ol6-agrac-rac2 ~]$ echo $PATH
/u01/app/oracle/product/11.2.0.3/db_1/bin:/usr/sbin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/bin:/usr/local/sbin:/usr/s
bin:/sbin:/home/oracle/bin
[oracle@ol6-agrac-rac2 ~]$
```